











	Item-No.	Description
	385/0	<b>VERIBOR Suction Lifter 1-point</b> aluminium body collapsible handle to operate with one hand suction cup 120 mm Ø loading capacity 30 kg (horizontal, according to supplier)
	385/0KU	<b>VERIBOR Suction Lifter 1-point</b> plastic body collapsible handle to operate with one hand suction cup 120 mm Ø loading capacity 30 kg (horizontal, according to supplier)
	385/2	<b>VERIBOR Suction Lifter 2-point</b> aluminium body suction cup 120 mm Ø loading capacity 40 kg (horizontal, according to supplier) loading capacity 70 kg (vertical, according to supplier)
	385/2KU	<b>VERIBOR Suction Lifter 2-point</b> plastic body suction cup 120 mm Ø loading capacity 60 kg (vertical, according to supplier)
	385/2G	<b>VERIBOR Suction Lifter 2-point - flexible</b> for curved surfaces plastic body suction cup 120 mm Ø loading capacity 45 kg (vertical, according to supplier)

	Item-No.	Description
	385/2GG	<b>VERIBOR Suction Lifter 2-point - flexible</b> for curved surfaces <b>with joints in longitudinal and vertical direction</b> plastic body suction cup 150 mm Ø loading capacity 45 kg (vertically, according to supplier)
	385/2WZ	<b>VERIBOR Suction Lifter 2-point - angular</b> for all smooth surfaces for fixing of mitres at showcases, aquariums, shop windows etc.  plastic body 2 articulated joints 90 degrees marking suction cup 120 mm Ø
	385/3	<b>VERIBOR Suction Lifter 3-point</b> aluminium body suction cup 120 mm Ø loading capacity 100 kg (vertical, according to supplier)
	385/ES110	<b>Spare Sucker</b> for VERIBOR 385/0
	385/ES120	<b>Spare Sucker</b> for VERIBOR 385/2+3 with bolt and tilting lever