

**Accu Device  
Kombi  
7011-VT**

**For operation on  
EC construction sites  
only permissible with  
mechanical holding device  
according to**



**for planar-stabilized, vertical lifting and transporting  
the simple, mains-independent compact device**

**Description**

- **1-circuit vacuum system**
- the vacuum circuit has a vacuum tank with nonreturn valve, vacuum switch and control vacuum meter
- **completely closed vacuum circuit**  
prevents loss of vacuum at power failure
- warning lamp and acoustic signal indicate insufficient vacuum
- multiple row arrangement of suction cups
- suction cups fixed directly on the frame
- distance of suction cups cannot be adjusted
- all suction cups lockable individually
- guide bows

**Vacuum Generation**

- built-in low maintenance rechargeable battery vacuum pump (dry running system)
- for rechargeable battery and line operation without change-over
- built-in accumulator charger for charging over night
- no change of rechargeable battery necessary
- no cable - no hose

**Control Means**

- ON/OFF directly at the device
- SUCTION/RELEASE via cable remote control  
optional  
via infrared remote control

**Suspension:** 2-fold crane string  
**Safe Working Load:** 600 kg  
**Colour:** yellow



vertical

<b>suitable for lifting</b>				
material properties	gastight			
surface	smooth			
e. g.	glass panes, sealed units, plastic and ceramic plates, coated boards			
<b>suction cup type</b>	<b>540</b>			<b>388</b>
<b>diameter</b> in action approx. mm	200			300
<b>suction cup quality</b>	rubber black abrasion possible upto 100° heat resistance			
<b>number of suction cups</b>	4	8	4	6
<b>frame size</b> approx. mm	1100 x 850			
<b>safe working load</b> on smooth and clean surface at 60 % vacuum kg	160	300	400	600
<b>dead weight</b> approx. kg	40			
<b>structural depth of frame</b> approx. mm	320			
<b>voltage</b> charger for battery	230 Volts 50/60 Hz 1Ph			
<b>item-no.: 7011-VT...</b>	<b>4-0920</b>	<b>6-0920</b>	<b>4-0910</b>	<b>6-0910</b>
<b>voltage</b> charger for battery	110 Volts 50/60 Hz 1 Ph			
<b>item-no.: 7011-VT...</b>	<b>4-0920-110</b>	<b>6-0920-110</b>	<b>4-0910-110</b>	<b>6-0910-110</b>
<b>other frame sizes</b>	on request			
<b>Accessories on request</b>				
<b>item-no.: 388-SCHUTZ</b>	protection cap for suction cup 388			
<b>item-no.: 540-SCHUTZ</b>	protection cap for suction cup 540			
<b>item-no.: 7003-DSFUS2</b>	infrared remote control → SUCTION/RELEASE			
<b>item-no.: 7003-DSFUST</b>	infrared remote control → SUCTION/RELEASE <i>only outside the EC</i>			

Also available as 2-circuit vacuum lifting device (Type 7211-VT)  
in accordance to EN 13155 / prEN 13035.

